

Compu-Spread CS-150RC

Standalone Dual Joystick Controller

10.2016



► **Dual 3-axis joystick console for manual control of multiple hydraulic actuators, as are used in Snow and Ice Control**

The Rexroth CS-150 RC joystick console is an ergonomically designed operator interface for the control of multiple hydraulic actuators, typically cylinders, on Snow and Ice Control vehicles. The full CANbus architecture facilitates connection of the console to the robust Rexroth BODAS controller, which in turn drives the system hydraulic valves and other devices.

The two 3 axis non-contact joysticks, each with a deadman switch, are fitted into a slim profile console for easy installation in tight cab spaces. The console allows installation of up to 6 auxiliary rocker switches for lighting, warning and other valve functions.

Hydraulic valve nulling and trimming are easily done with the joysticks and a console switch, or with the optional nulling pendant.



► **CS-150 RC nulling pendant**

CS-150 Joystick & console features

- Hall effect joysticks with integrated CANbus output
- Joystick dead-man switch prevents inadvertent and unwanted actuator movements
- Low profile joysticks require limited movement and low operating force
- Backlit console legends for joystick identification
- Simple power float mode supported
- Dump Limit supported
- Valve trimming and nulling can be done with a separate control box (optional), which is then set aside
- Wiring harnesses have integral moulded diagnostic LEDs
- All functions are configurable
- Standard Scraper Auto-raise function when vehicle transmission goes into reverse

Technical Data

Joystick				
Mechanical (for X, Y axes)	Break-out force:	1.8N (0.4 lbf)	Expected life:	10 million cycles
	Operating force:	3.5N (0.75 lbf)	Material:	Glass filled nylon
	Maximum applied force:	450 N (100 lbf)	Lever action:	Spring centring
	Mechanical angle of movement	40°		
Mechanical (for Z axis)	Break-out torque:	0.09 Nm (0.80 lbf-in)	Hand mechanical angle:	80° (40° from centre)
	Operating torque:	0.121 Nm (1.07 lbf-in)	Handle action:	spring centring
	Max. allowable torque:	0.150 Nm (1.33 lbf-in)	Expected life:	10 million cycles
Sealing (IP)	IP 65			
EMC Immunity Level (V/M)	IEC 61000-4-3: 2006			
EMC Emissions Level	IEC 61000-4-8: 1993/A1: 2000			
ESD	IEC 61000-4-2: 2008			

CS-150RC System Electrical & Environmental Specifications

Supply Voltage	9-32 VDC			
Outputs	Proportional outputs	12 channels		
	Digital Outputs	4 channels		
Inputs (All inputs protected and filtered)	Switched Inputs	6 channels		
	Analogue Voltage Inputs	20 channels		
	Analogue Current Inputs	4 channels		
Interfaces	1 CAN port, CAN 2.0B			
Operating Temperature	-30°C to 85°C	-22°F to 185°F		
Storage Temperature	-40°C to 85°C	-40°F to 185°F		

Compliant Standards RC Controller (for more BODAS Controller series 20 details refer to Rexroth data sheet RE 95 200)

Electromagnetic Compatibility	100v/m, load dump ISO 7637-2 (2004) pulse 5			
Immunity	RF Immunity:	ISO 11452-2, 400-1000 MHz, 80% mod.1kHz 1 GHz–2 GHz, 80% mod. 1 kHz 25v/m (Level 1 Severity)		
	Conducted Immunity:	ISO 7637-2 (2004), System Pulse 1, 2a, 2b, 3b, 4		
RF Emissions	CISPR 25:2002-08, 30 MHz–1 GHz, according to 72/245/EC EN 55025			
Electrostatic Discharge	EN 61000-4-2 ISO 10605, Contact +/- 8kV, air discharge +/- 15kV			
Vibration	ISO 16750-3, 10-2000Hz @ 58 m/s			
Shock	IEC 60068-2-72, 40G for 11 ms			
Moisture	DIN IEC 68, part 2, Hum=95% 25 to –55°C			
Salt Spray	DIN 50021-SS, 72h 35°C 5% NaCl			
Media Resistance	ISO 16750-5, cola, coffee, paint thinner			
Enclosure Protection	IEC 60529 IP56			

Bosch Rexroth Canada
490 Prince Charles Drive S
Welland, ON L3B 5X7
Phone: (905) 735-0510
Toll Free: 1-877-COMPU-11
info@boschrexroth.ca
www.boschrexroth.ca/cs

© Bosch Rexroth Canada Corp.
This document, as well as the data, specifications and other information set forth in it, are the exclusive property of Bosch Rexroth. It may not be reproduced or given to third parties without its consent. The data specified above only serve to describe the product. No statements concerning a certain condition or suitability for a certain application can be derived from our information. The information given does not release the user from the obligation of own judgment and verification. All products described in this data sheet are subject to normal aging and wear from usage. Subject to change